


KWC FIT Lever mixer – Kitchen

Modell-Linie: FIT | 10.541.032.176FL

Taps | Manual taps





KWC-No.

125572

chromeline, A 205, flexible connection hoses

125573 matt black, A 205, flexible connection hoses

- * Lever mixer
- * TouchProtect anti-scald protection thanks to the "double skin"

- TouchProtect anti-scala protection thanks to the "aouble skir principle
 Intrinsically safe against backflow
 Pull-out spray
 up to 500 mm pull-out length
 QuickConnect Simple hose connection system
 * Hose guide, swivelling 120°
 * EasyLock a pull-out spray that easily slides back into place
- А

* KWC cartridge M 35 S

* Mounting hole size ø35 mm



NEW

Technical Data Energy Label

| Flow rate needle spray | |
|-------------------------|--|
| Flow fate fleedle spray | |
| Flow rate normal spray | |
| Connection | |
| Spout | |
| Handling | |
| Kitchenspray | |
| Color_code | |
| Installation type | |
| Faucet_typ | |
| Acoustic group | |
| Projection_A | |

| A | |
|-------------------|--|
| 6.5 l/min (3 bar) | |
| 6.8 l/min (3 bar) | |
| Thermosatic | |
| 2 | |
| Shut-off valve | |
| Shut-off valve | |
| matt black | |
| Shut-off valve | |
| Lever mixer | |
| Shut-off valve | |
| A 205 | |

with ceramic discs
 with ceramic discs
 flow rate and temperature continuously variable
 temperature limitation
 * Flexible connection hoses %"
 * QuickInstallation - Fastening via threaded connection with locking