

Order number: 01 113 06 99

## SCHELL infrared urinal flush valve unit SCHELLTRONIC

WELL A Public  
exposed urinal flush for battery operation with isolating valve

### Scope of delivery:

- 6 V solenoid valve in cartridge design with integrated pre-filter
- internal attachment connector
- flush pipe 18 x 200 mm
- 9 V alkaline battery

### Field of application / Technical data:

- flow pressure: 0,5 to 5 bar
- flow volume: 0,3 l/s according to DIN EN 12541
- flush time: 2 - 15 seconds adjustable
- stagnation flush every 24 hours after last flush

### Details:

- Material:
  - parts in contact with water conform German drinking water regulation
- Surface: chrome
- Weight: 1.24 kg/pc.
- Packaging unit: 1
- Dimension: DN 15 G 1/2 ext. thread

### Versions:

Dimension: DN 15 G 1/2 ext. thread  
chrome, PU 1, W: 1.24 kg/pc.

Order No.: [01 113 06 99](#)

### Recommended associated item:

Flush pipe Ø 18 mm  
Flush pipe Ø 18 mm edged  
Flush pipe Ø 18 mm edged  
External connector  
urinal mounting module

Order No.: [50 722 06 99](#) or  
Order No.: [50 223 06 99](#) or  
Order No.: [50 291 06 99](#)  
Order No.: [27 820 06 99](#)  
Order No.: [03 272 00 99](#)

