

Order number: 02 477 06 99

SCHELL urinal flush valve SCHELLOMAT BASIC, DN 15

robust all-metal flush valve unit with brass pushbutton high reliability thanks to plastic cartridge and integrated jet bore pre-filter flush unit according to DIN EN 12541

SCHELLOMAT BASIC SV with integrated isolating valve

Scope of delivery:

- flush pipe \varnothing 18 x 200 mm
- push rosette
- internal flush pipe connector

Field of application / Technical data:

- flow volume: 0,3 l/s
- flow pressure: 0,8 - 5,0 bar
- flush volume adjustable 1 – 6 l

Details:

- Material: all parts in contact with water out of brass conform German drinking water regulation, functioning parts cartridge plastic
- Test Mark: PA-IX 9892/II, DIN-DVGW certified
- Surface: chrome
- Weight: 0.72 kg/pc.
- Packaging unit: 1
- Dimension: DN 15 G 1/2 ext. thread

Versions:

Dimension: DN 15 G 1/2 ext. thread
without isolating valve, chrome, PU 1, W: 0.7 kg/pc.

Order No.: [02 476 06 99](#)

Dimension: DN 15 G 1/2 ext. thread
SCHELLOMAT BASIC SV with integrated isolating
valve, chrome, PU 1, W: 0.72 kg/pc.

Order No.: [02 477 06 99](#)

Recommended associated item:

urinal mounting module

Order No.: [03 272 00 99](#)

