

Order number: 02 238 06 99

SCHELL WC flush valve unit SCHELLOMAT

with lever

flow rate: 1,0 - 1,3 l/s, cartridge with piston out of brass

Scope of delivery:

- Lever mit test
- flow rate regulator
- automatic jet cleaning needle, flush unit with anti-vacuum device according to DIN EN 12541

Field of application / Technical data:

- shallow and deep pans
- flow pressure: from 1,2 bar
- flow volume: 6 l
- for flush pipe \varnothing 28 x 26 mm

Details:

- Material: piston out of dezincification-resistant brass
- Surface: chrome
- Weight: 0.63 kg/pc.
- Packaging unit: 1
- Dimension: DN 20 G 3/4 ext. thread

Versions:

Dimension: DN 20 G 3/4 ext. thread	Order No.: 02 202 06 99
Flow rate: 1.0 - 1.3 l/s, PA-IX 18853/II, DIN-DVGW certified, Belgaqua, chrome, PU 1, W: 0.6 kg/pc.	
Dimension: DN 20 G 3/4 ext. thread	Order No.: 02 238 06 99
flow rate: 1,0 - 1,3 l/s, cartridge with piston out of brass, chrome, PU 1, W: 0.63 kg/pc.	
Dimension: DN 15 G 1/2 ext. thread	Order No.: 02 216 06 99
flow rate: 0,7 - 1,0 l/s, chrome, PU 1, W: 0.63 kg/pc.	

Recommended associated item:

WC pipe connection kit	Order No.: 03 209 06 99	or
WC flush pipe	Order No.: 03 100 06 99	

