

Order number: 01 548 28 99

SCHELL WC control EDITION E

battery operation/mains operation

contact-free infrared flush valve automatic actuation when leaving the WC (room monitoring) E-module prepared for connection of switch module single/dual flush for external actuation finishing set WC electronic with front panel out of stainless steel for SCHELL WC concealed flush valve COMPACT II

Scope of delivery:

- mounting frame with electronic module
- front panel with sensor window
- bistable cartridge solenoid valve 6 V
- plastic cartridge with automatic jet cleaning needle

Field of application / Technical data:

- single flush: 6 l factory setting, 3,5 - 9 l adjustable
- stagnation flush every 24 h after last flush
- room monitoring 400 - 800 mm adjustable
- flush volume regulation by means of pressure plate (pre-assembled)

Details:

- Material: front panel stainless steel
- Surface: stainless steel
- Weight: 1.26 kg/pc.
- Packaging unit: 1

Required associated item:

concealed WC flush valve COMPACT II	Order No.: 01 194 00 99	or
concealed transformer 100 - 240 V, 50 - 60 Hz, 12 V	Order No.: 01 566 00 99	or
transformer 100 - 240 V, 50 - 60 Hz / 12 V	Order No.: 01 490 00 99	or
electric junction box	Order No.: 01 537 00 99	
connection cable	Order No.: 01 542 00 99	or
connection cable	Order No.: 01 543 00 99	
battery compartment 9 V	Order No.: 01 853 00 99	or

Recommended associated item:

switch module for single flush	Order No.: 01 170 06 99	or
switch module for dual flush	Order No.: 01 169 06 99	

