

Order number: 02 170 06 99

## SHELL electronic wash basin tap MODUS Trend E

(high-pressure mixed water)

Battery operation with external battery compartment and 4x AA alkaline batteries

### Scope of delivery:

- infrared sensor single hole tap
- electronics programmable
- connection cable (250 mm) with plug protection class IP 65
- solenoid valve
- 2 flexible hoses G 3/8 int. thread x 450 mm with backflow preventer (BP, DIN EN 1717:EB) and prefilter
- flow regulator
- wash basin mounting accessories

### Field of application / Technical data:

- flow volume: max. 3 l/min independent of pressure
- flow pressure: 0,5 - 5 bar
- max. resting pressure 8 bar
- water temperature max. 70°C (briefly e.g. for thermal disinfection)

### Adjustable via hand programming:

- sensor range  $\approx$  2 - 17 cm
- cleaning stop 120 s

### Details:

- Material: Housing out of brass conform German drinking water regulation
- Test Mark: P-IX 29853/IO
- Noise Class: 1
- Surface: chrome
- Weight: 0 kg/pc.
- Packaging unit: 1
- Dimension: 2x G 3/8 int. thread

### Versions:

Dimension: 2x G 3/8 int. thread      Order No.: [02 171 06 99](#)  
 Mains operation, with power supply unit 6 V, chrome,  
 PU 1

### Recommended associated item:

angle valve with regulating function COMFORT with filter      Order No.: [05 430 06 99](#)  
 Flow regulator 1.33 l/min (2 or 6 LEED points)      Order No.: [05 430 06 99](#)    or  
 Flow regulator 5,00 l/min      Order No.: [05 430 06 99](#)

