



German  
Design Award  
SPECIAL  
MENTION 2014

PIA'13 PRODUCT INNOVATION  
AWARD WINNER

DESIGN PLUS

KWC-No.	Finish
<b>10.201.122.000FL</b>	all chrome
A 215, flexible connection hoses, mains receiver	

## Kitchen with LEDShine

### Lever mixer

- Lever installation only possible on the right side
  - Child safety: cold water flow in lever position towards the front
- gap between wall and centre of mounting hole min. 42 mm
- TouchProtect - anti-scald protection thanks to the "double skin" principle
- Covered pull-out spray
  - ergonomic spout alignment, shape and handling
  - SprayClean - easy to clean and actively prevents limescale buildup
  - Neoperl® Cascade®
  - PowerClean - needle spray mode, with automatic diverter reset
  - integrated ON/OFF push-button with automatic shut-off after 30 minutes
  - up to 500 mm pull-out length
  - hose surface to fit faucet surface
- SwivelStop - hose guide, swivelling 270°, limitable to 120°
- EasyLock - a pull-out spray that easily slides back into place
- OptimalSpace - ample space for washing or working
- KWC cartridge S 25
  - with ceramic discs
  - flow rate and temperature continuously variable
- Flexible connection hoses 3/8"
- Fastening by means of threaded sleeve M33 x 1.5
- Mounting hole size ø35 mm
- Scope of delivery:
  - Mains receiver 100-240 V / operating voltage 6.75 V / cable length 1100 mm

Flow rate normal spray 8 l/min (3 bar)

Flow rate needle spray 9 l/min (3 bar)

Acoustic group II

Subject to technical, range and model changes. Dimensions in mm.