



KWC-No.	Finish
<b>10.661.003.000FL</b>	all chrome

A 215, flexible connection hoses

## Kitchen

### Lever mixer

- Lever installation only possible on the right side
  - Child safety: cold water flow in lever position towards the front
- gap between wall and centre of mounting hole min. 26 mm
- TouchProtect - anti-scald protection thanks to the "double skin" principle
- Intrinsicly safe against backflow
- Pull-out spray
  - SprayClean - easy to clean and actively prevents limescale buildup
  - up to 600 mm pull-out length
  - TripleClean - Normal, soft, and power stream modes
  - hose surface to fit faucet surface
  - QuickConnect - Simple hose connection system
- Hose guide, swivelling 150°
- EasyLock - a pull-out spray that easily slides back into place
- OptimalSpace - ample space for washing or working
- KWC cartridge M 35 S
  - with ceramic discs
  - flow rate and temperature continuously variable
  - temperature limitation
- Flexible connection hoses 3/8"
- QuickInstallation - Fastening via threaded connection with locking screws
- Mounting hole size  $\varnothing 35$  mm
- To be ordered separately (optional or if necessary):
  - Swivel range limited to 120°, Z.538.320

Flow rate normal spray 8 l/min (3 bar)

Flow rate needle spray 8 l/min (3 bar)

Acoustic group I

Subject to technical, range and model changes. Dimensions in mm.