



KWC-No.	Finish
10.481.002.127FL	decor steel

A 220, flexible connection hoses

Kitchen

Lever mixer

- Lever installation only possible on the right side
 - Child safety: cold water flow in lever position towards the front
- gap between wall and centre of mounting hole min. 26 mm
- TouchProtect - anti-scald protection thanks to the "double skin" principle
- Pull-out spray
 - ergonomic spout alignment, shape and handling
 - SprayClean - easy to clean and actively prevents limescale buildup
 - Neoperl® Perlator® laminar
 - PowerClean - needle spray mode, with automatic diverter reset
 - up to 500 mm pull-out length
- Hose guide, swivelling 150°, can be extended to 360°
- EasyLock - a pull-out spray that easily slides back into place
- OptimalSpace - ample space for washing or working
- KWC cartridge M 35 S
 - with ceramic discs
 - flow rate and temperature continuously variable
- Flexible connection hoses 3/8"
- QuickInstallation - Fastening via threaded connection with locking screws
- Mounting hole size ø35 mm
- To be ordered separately (optional or if necessary):
 - Swivel range limited to 120°, Z.538.320

Flow rate normal spray 10 l/min (3 bar)
 Flow rate needle spray 9 l/min (3 bar)
 Acoustic group I

Subject to technical, range and model changes. Dimensions in mm.