



KWC-No.	Finish
<b>10.481.232.000FL</b>	all chrome

A 220, flexible connection hoses, mains receiver

## Kitchen with LED-technology

IntelligentControl - electronic control

- gap between wall and centre of mounting hole min. 26 mm
- TouchProtect - anti-scald protection thanks to the "double skin" principle
- Microprocessor-control
  - touch'n'flow 1: cold water, 50% flow rate can be individually adjusted and saved
  - touch'n'flow 2: warm water, 50% flow rate can be individually adjusted and saved
  - touch'n'flow 3: hot water, 50% flow rate can be individually adjusted and saved
  - with cleaning programme
- Pull-out spray
  - ergonomic spout alignment, shape and handling
  - SprayClean - easy to clean and actively prevents limescale buildup
  - Neoperl® Perlator® laminar
  - PowerClean - needle spray mode, with automatic diverter reset
  - Integrated control unit
  - up to 500 mm pull-out length
  - hose surface to fit faucet surface
- Hose guide, swivelling 150°, can be extended to 360°
- EasyLock - a pull-out spray that easily slides back into place
- OptimalSpace - ample space for washing or working
- KWC control unit, maintenance-free
  - up-to-date microprocessor and drive technology
  - tried-and-tested valve technology
  - without installation materials
  - designed for wired connection to 1 operating unit (standard)
- Flexible connection hoses 3/8"
- QuickInstallation - Fastening via threaded connection with locking screws
- Mounting hole size ø35 mm
- Scope of delivery:
  - Mains receiver 100-240 V / operating voltage 12 V / cable length 2000 mm

- To be ordered separately (optional or if necessary):
  - Swivel range limited to 120°, Z.538.320