



KWC-No.	Finish
10.481.232.176FL	matt black

A 220, flexible connection hoses, mains receiver

Kitchen with LED-technology

IntelligentControl - electronic control

- gap between wall and centre of mounting hole min. 26 mm
- TouchProtect - anti-scald protection thanks to the "double skin" principle
- Microprocessor-control
 - touch'n'flow 1: cold water, 50% flow rate can be individually adjusted and saved
 - touch'n'flow 2: warm water, 50% flow rate can be individually adjusted and saved
 - touch'n'flow 3: hot water, 50% flow rate can be individually adjusted and saved
 - with cleaning programme
- Pull-out spray
 - ergonomic spout alignment, shape and handling
 - SprayClean - easy to clean and actively prevents limescale buildup
 - Neoperl® Perlator® laminar
 - PowerClean - needle spray mode, with automatic diverter reset
 - Integrated control unit
 - up to 500 mm pull-out length
- Hose guide, swivelling 150°, can be extended to 360°
- EasyLock - a pull-out spray that easily slides back into place
- OptimalSpace - ample space for washing or working
- KWC control unit, maintenance-free
 - up-to-date microprocessor and drive technology
 - tried-and-tested valve technology
 - with-out installation materials
 - designed for wired connection to 1 operating unit (standard)
- Flexible connection hoses 3/8"
- QuickInstallation - Fastening via threaded connection with locking screws
- Mounting hole size ø35 mm
- Scope of delivery:
 - Mains receiver 100-240 V / operating voltage 12 V / cable length 2000 mm
- To be ordered separately (optional or if necessary):

– Swivel range limited to 120°, Z.538.320