

Article number: 02 157 06 99

## Self-closing wash basin taps XERIS SC HD-M mid - high-pressure mixed water

Manual actuation with automatic closing. Easy flow time adjustment.



### Scope of delivery


- Self-closing single-hole tap
  - Self-closing cartridge SC II with hot water restrictor
  - Flow regulator
- 2 flexible Clean-Fix S connection hoses, G 3/8 IG x 380 mm, with integrated backflow preventer (EN 1717: EB-type) and pre-filter
- Fastening material for wash basin installation

### Technical data

- Running time: 2 - 15 s (7 s)
- Flow: max. 5 l/min pressure independent
- Flow pressure: 1.0 - 5.0 bar
- Max. Resting pressure: 8 bar
- Max. operating temperature: 70 °C (80 °C for thermal disinfection)
- Material: Housing Brass, conform to German drinking water regulations
- Surface: Chrome
- Connection: 2x G 3/8 IG
- Certificates: PA-IX 29071/IO, ACS, Belgaqua
- Noise class: I
- Flow class: O

### Delivery data

- Weight: 2,05 kg/Piece
- Packing unit: 1



### Recommended associated articles

Angle valve thermostat	Article no: 09 414 06 99
Pressure balance valve (PBV)	Article no: 06 558 12 99
Angle valve with regulating function COMFORT with filter	Article no: 05 430 06 99